




DOVETAILS ALLOW STACKING IN VERTICAL, HORIZONTAL, OR IN BLOCK CONFIGURATIONS.

| COLOR | P/N |
|--------|-----------|
| RED | MN1327 |
| GREEN | MN1327G5 |
| BLACK | MN1327G6 |
| WHITE | MN1327G7 |
| BLUE | MN1327G8 |
| YELLOW | MN1327G16 |
| ORANGE | MN1327G17 |
| GRAY | MN1327G18 |
| BROWN | MN1327G21 |

MATED PAIR

R 1.3
SEE NOTE 2

1. THESE HOUSING ASSEMBLIES ACCOMMODATE METALTEX CONTACTS FOR WIRE RANGES FROM 1MM² (#17AWG) TO 6MM² (#10 AWG).
2. WHEN MATED SIDE TO SIDE, HALF-ROUNDS ALIGN TO FORM A SLOT FOR ROLL PIN INSERTION, WHICH PROTECTS AGAINST ACCIDENTAL DISLODGING OF MATED HOUSINGS.

| | | | | | |
|--|---|---|-----------------------------|-----------|-----------------|
| DIMENSIONS ARE IN: MM | |  | | | |
| UNLESS OTHERWISE STATED | | | | | |
| TOLERANCES: DECIMALS (MM) ANGLES .X ± .5 ±2 ° | | <div>MN15/45 series unipolar housings (with integrated contact retention springs)</div> | | | |
| MATERIAL: SPRINGS: STAINLESS STEEL HOUSINGS: PC, UL94 V-0 | | | | | |
| FINISH: | | | | | |
|  3rd ANGLE PROJECTION |  | SCALE NONE | DWG NO. MN15_45_Housings | REV. 0 | SHEET 1 OF 1 |