











COLOR	P/N
 BLUE	<b>MN5916</b>
 BLACK	<b>MN5916G4</b>
 WHITE	<b>MN5916G5</b>
 GREEN	<b>MN5916G6</b>
 RED	<b>MN5916G7</b>
 ORANGE	<b>MN5916G14</b>
 GRAY	<b>MN5916G16</b>

MATED PAIR

1. THESE HOUSING ASSEMBLIES ACCOMMODATE METALTEX CONTACTS FOR WIRE RANGES FROM 6MM<sup>2</sup> (#10 AWG) TO 16MM<sup>2</sup> (#6 AWG).
2. WHEN MATED SIDE TO SIDE, HALF-ROUNDS ALIGN TO FORM A SLOT FOR ROLL PIN INSERTION, WHICH PROTECTS AGAINST ACCIDENTAL DISLODGING OF MATED HOUSINGS.

DIMENSIONS ARE IN: MM					
UNLESS OTHERWISE STATED					
TOLERANCES: DECIMALS (MM) ANGLES .X ± .5    ±2 °		<b>MN75 series unipolar housings</b> <b>(with integrated contact retention springs)</b>			
MATERIAL: SPRINGS: STAINLESS STEEL HOUSINGS: PC, UL94 V-0					
FINISH:					
		SCALE NONE	DWG NO. <b>MN75_Housings</b>	REV. <b>0</b>	SHEET <b>1 OF 1</b>